

DS-D42V16-N



The DS-D42V16-N is all-in-one controller that integrates video processing, video control and LED screen configuration into one unit. Together with video control software , it enables richer image mosaic effects and easier operations.

- 16 Ethernet output ports load up to 10,400,000 pixels
- Up to 4 DVI inputs can form an independent input source, which is DVI Mosaic
- Supported frame rates include 23.98 Hz, 29.97 Hz, 47.95 Hz, 59.94 Hz, 71.93 Hz and 119.88 Hz.
- Up to 4 devices can be linked to load a super large screen when used together with the video distributor
- Up to 10 presets can be saved for future use
- Custom EDID and standard EDID supported
- In backup mode, when the signal is lost or the Ethernet port fails on the primary device, the backup device will take over the task seamlessly

▪ Specification



Model		DS-D42V16-N
Interface	Video & Audio Input	/
	Video & Audio Output	/
	Network Interface	16
	Control Interface	RJ45 × 1, USB (Type-B) × 1
Processing Performance	Max. Load Capacity	10400000 pixels
	Frame Frequency	50/60 Hz
	Refresh Rate	60 HZ
	Processing Depth	8 bit
	Grey Level	16 bit
	Display Color	281 trillion
	Brightness Control	0 to 255 adjustable
	Max. Resolution of Bar Display	16384 x 8192 pixels
Power	Max. Consumption	70 W
	Average Consumption	23 W
	Input Voltage	100-240V
Working Environment	Working Temperature	0°C to 50°C
	Working Humidity	20% to 85% RH (non-condensing)
	Storage Temperature	-20°C to +60°C
	Storage Humidity	10% to 85% RH (non-condensing)
General	Product Dimensions (W × H × D)	482.6 mm × 372.5 mm × 94.6 mm
	Package Dimensions (W × H × D)	530.0 mm × 420.0 mm × 193.0 mm
	Net Weight	6.22 Kg

	Gross Weight	9.78 Kg
	Packing List	1x European power cord , 1x US power cord, 1x UK power cord, 1x Cat5e, Ethernet cable, 1x USB cable, 1x DVI cable, 1x HDMI cable, 1x Quick Start Guide , 1x Certificate of Approval

▪ Available Model

DS-D42V16-N(海外标配),

▪ Dimension





Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

